

19" LCD Open Frame Touch Monitor

ST-HB19A2L

Specifications

LCD PANEL

Brightness	240 cd/m ² (Typ.)
Contrast Ratio	400:1
Viewing Angle	H:170° / V:170°
Response Time	21 ms (Tr + Tf)
Supported colors	16.7M colors
Resolution	1280 x 1024

DISPLAY FEATURES

Horizontal Frequency	22 ~ 82KHz
Vertical Frequency	50 ~ 76Hz
Input Resolution	1280 x 1024 @ 79.9Hz (Analog)
DDC	DDC 2B Compliance
OSD Control	Push button
OSD Language	English, French, German, Russian, Japanese, Traditional Chinese Simplified Chinese, Spanish, Italian
Video Signal Type	RGB Analog

PHYSICAL FEATURES

Connector	15 pin D-Sub
Dimension	443.4 x 329.9 x 65.8 mm (WxHxD)
Diagonal	19"
Weight W/O Stand	4.4 kg
Wall Mount Type	100mm x 100mm VESA Front Side Mount

SPECIAL FEATURES

Audio in	3.5mm Phone Jack
Audio out	2.5 W
Fanless design	Yes

TOUCH FEATURES

Technology	5-wire Resistive
Method	Finger, stylus, or any other pointer
Response Time	≤ 10 ms
Interface	USB, Plug-and-Play compatible
Operating Systems	Windows 95 / 98 / 2000 / ME / XP, Windows NT, DOS

POWER CONSUMPTION

Power Supply	AC 100V ~ 240V
Normal operation	65 W
Stand by Mode	3 W



*All specifications subject to change without notice.

Dimensions

