

32" High-Definition LCD Panel Display

ST-HB32A1X

Specifications

LCD PANEL	
Brightness	500 cd/m ²
Contrast Ratio	1200:1
Viewing Angle	H:176° / V:176°
Response Time	6.5ms (GTG)
Supported colors	16.7M colors
Resolution	1366 x 768 (16:9)

DISPLAY FEATURES	
Horizontal Frequency	30K ~ 65KHz
Vertical Frequency	56 ~ 75Hz
Input Resolution	1360 x 768 @ 60Hz (Analog) 1360 x 768 @ 60Hz (Digital)
DDC	DDC 2B
OSD Control	RS232C, Push button, IR Remote Controller
OSD Language	English

PHYSICAL FEATURES	
Connector	15 pin D-Sub / DVI / Component / S-video / AV
Dimension W/O Stand	790.2 x 480.2 x 82 mm (WxHxD)
Weight W/O Stand	Net: 15kg Gross: 18.5kg
Wall / Arm Mount Type	100mm x 100mm / 200mm x 200mm VESA

SPECIAL FEATURES	
Multimedia	PIP, PAP, Zoom
Audio In/Out	N/A
Fanless design	No
Source auto detect	Yes

POWER CONSUMPTION	
Power Supplier	AC 100V ~ 240V (50 / 60 Hz)
Normal Operation	less then 180W
Suspend / Standby	less then 20W
Power off Mode	less then 20W

ENVIRONMENTAL	
Operating Temperature	5°C~40°C
Storage Temperature	-20°C~60°C
Operating Humidity	85%RH
Storage Humidity	85%RH

OPTIONS	
Protective surface	4mm glass (AG/AR), Tempered Glass
Communication port (Transport Protocol)	D-Sub 9 Pin, RJ45 In/Out (RS-232, RS-485 In/Out)



Dimensions

